

X-1800SD

REEL-TO-REEL, CARTRIDGE STEREO TAPE RECORDER



- OPEN REEL: 4-TRACK STEREO/MONAUROAL RECORDING /PLAYBACK SYSTEM
- CARTRIDGE: 8-TRACK STEREO RECORDING/PLAYBACK SYSTEM
- TRANSFER FROM REEL TO CARTRIDGE
- REEL: CROSS-FIELD HEAD
- CARTRIDGE: ONE MICRON GAP HEAD
- ONE HOUR CONTINUOUS CARTRIDGE STEREO PERFORMANCE
- OUTPUT POWER: TOTAL 12 W

SPECIFICATIONS

Transistors: 19

Dimensions: 13-1/2"(W) × 15"(H) × 9-1/2"(D) (338 × 378 × 238mm)

Weight: 37.4 lbs. (17 kg)

REEL-TO-REEL

Tape Speed: 1-7/8, 3-3/4 and 7-1/2 ips (15 ips w/adapter)

Wow/Flutter: Less than 0.12% RMS at 7-1/2 ips

Frequency Response: 30 to 20,000 Hz (± 3 dB) at 7-1/2 ips

S/N Ratio: Better than 50 dB

CARTRIDGE

Tape Speed: 3-3/4 ips

Wow/Flutter: Less than 0.25% RMS

Frequency Response: 50 to 17,000 Hz (± 3 dB)

S/N Ratio: Better than 45 dB