

2500

THREE MOTORS/FOUR HEADS/AUTO
REVERSE TAPE DECK



■ 4-TRACK STEREO/MONAUROAL RECORDING/PLAYBACK SYSTEM ■ AUTOMATIC CONTINUOUS REVERSE ■ THREE SPEED SERVO-CONTROLLED OUTER-ROTOR MOTOR WITH DIRECT CAPSTAIN DRIVE ■ AUTOMATIC TAPE LIFTER ■ REEL RETAINERS ■ AUTOMATIC STOP/SHUT-OFF ■ PAUSE BUTTON WITH LOCK ■ EASY SOUND-ON-SOUND OPERATION ■ REMOTE CONTROL WITH RC-16 REMOTE CONTROL UNIT

SPECIFICATIONS

Tape Speed: 1-7/8, 3-3/4 and 7-1/2 ips

Wow/Flutter: Less than 0.08% RMS at 7-1/2 ips

Frequency Response: 30 to 22,000 Hz (± 3 dB) at 7-1/2 ips

Distortion: Within 2% at 7-1/2 ips (1,000 Hz "0" VU Recording)

S/N Ratio: Better than 50 dB

Transistors: 34

Dimensions: 17.1"(W) \times 18.1"(H) \times 10.1"(D) (435 \times 460 \times 260 mm)

Weight: 44.1 lbs. (20 kg)